

Telemecanique
XVP Illuminated Indicating Banks
Ø 50mm

*“Minimum size,
Maximum efficiency”*



XVP Illuminated Indicating Banks

A *solution* for *any type* of *installation*

Having a **high degree of protection (IP65)** and providing **strong brightness** together with **excellent reliability**, particularly when used with LED light sources, makes the XVP Indicating Banks suitable for any type of environment.

Their compactness (Ø 50mm) also makes them particularly suitable for use on small equipment.



Perfect modularity

- Variable composition of up to 5 units.
- Interchangeable, stackable units with simple assembly.
- Electrical connections automatically made between units.
- Interlocking and unlocking of units by clamping ring.




Illuminated units for BA 15d bulb

steady light
incandescent bulb
or LED **not included**



Illuminated units with Strobe

0,6 to 2Hz
-




Audible units, multidirectional

continuous/intermittent tone
adjustable: 55...85 dB
at 1m



Base units + cover

with cable entry through bottom, for wires
with or without cable end



Support tube with integral fixing base
Aluminium

12 to 230V	~ 24V (0,3 joules)	~ 24V	with or without cable end	100mm (4")
Black XVP-C3●	Black XVP-C6B●	Black XVP-C09B	Black XVP-C21	Black XVP-C02
Cream XVP-C3●W	Cream XVP-C6B●W	Cream XVP-C09BW	Cream XVP-C21W	Cream XVP-C02W
	~ 120V (0,6 joules)	~ 120V		250mm (10")
	Black XVP-C6G●	Black XVP-C09G	for Ring-Tongue Terminals	Black XVP-C03
	Cream XVP-C6G●W	Cream XVP-C09GW	Cream XVP-C21WR	Cream XVP-C03W
	~ 230V (0,6 joules)	~ 230V		400mm (16")
	Black XVP-C6M●	Black XVP-C09M		Black XVP-C04
	Cream XVP-C6M●W	Cream XVP-C09MW		Cream XVP-C04W

• **To complete the reference for an illuminated unit:** Replace the ● by the number indicating the required color, as shown below.

■ 3 = green ■ 4 = red ■ 5 = orange ■ 6 = blue □ 7 = clear ■ 8 = yellow

Example: Unit with black clamping ring incorporating ~ 120V red Strobe element = **XVP-C6G4**

Aesthetic well suited and original


- Two housing colors: black and off-white (cream)
- Six illuminated unit colors: green, red, orange, blue, clear and yellow.



Choice of signalling

- Steady or Strobe light for illuminated units: incandescent bulbs or BA15d base mounted LEDs (steady or flashing).
- 10 selectable continuous or intermittent tones for audible units.


Conformity to international standards




Threaded support tube with bracket
Metal



Right Angle Mount
for use on vertical surface



Bulb removal tool



Incandescent bulbs



LEDs

				BA 15d base fitting steady light	BA 15d base fitting steady light
100mm (4")				24V 4W DL1-BEBS	24V DL1-BDB●
XVP-C02T	Black	XVP-C12	XVP-CX13	120V 5W DL1-BEGS	120V DL1-BDG●
	Cream	XVP-C12W		230V 5W DL1-BEMS	230V DL1-BMB●
250mm (10")				steady light	flashing light
XVP-C03T				12V 7W DL1-BEJ	24V DL1-BKB●
				24V 6,5W DL1-BEB	120V DL1-BKG●
				48V 6W DL1-BEE	230V DL1-BKB●
400mm (16")				120V 7W DL1-BEG	
XVP-C04T				230V 7W DL1-BEM	

● To complete the reference for a BA 15d base mounted LED: Replace the ● by the number indicating the required color, as shown below.

□ 1 = white ■ 3 = green ■ 4 = red ■ 6 = blue ■ 8 = orange

Example: 120V, steady light, red LED = **DL1-BDG4**

A complete offer *of long distance* signalling units

*Select the units best suited
to your applications...*

- Industrial buildings, hospitals...
- Semi-conductor industry, packaging, conveyor...
- Infrastructures, transport...

Worldwide availability

With a presence in 130 countries, Schneider emphasises its desire to be close at hand.

In this way, you can benefit from the complete availability of the XVP range and all other long distance signalling units. You also have at your disposal all Schneider products, services and solutions anywhere in the world, thanks to 5,000 sales outlets and 800 industrial and commercial centers.



Square D Company / Schneider Electric

North American Headquarters

1415 South Roselle Road
Palatine, IL 60067
www.SquareD.com