

Harmony XVC Tower Lights



The new Schneider Electric line of Harmony XVC Tower Lights offer pre-wired, one piece construction with five color combinations and integrated buzzer options in 40mm, 60mm and 100mm diameters. The entire XVC range meets IP54 (NEMA 12 and 3R) degree of protection.

Save installation time and money with the pre-wired, color coded, one piece construction configuration and eliminate the need to select and wire individual colored lenses, buzzers and lamps.

Features:

- Up to 5 illuminated signaling units
- Steady light or flashing Superbright™ LEDs
- Available in red, orange, green, blue or clear
- Available with or without an audible buzzer (up to 85 decibels)
- 3 screws for base mounting or aluminum support tube with a bracket
- IP54 (NEMA 12 and 3R), UL508 Listed, CSA certified and CE marked

Product Offering:

Complete, pre-wired Tower Lights Ø 40mm Diameter					
Description	Light Source (included)	Voltage V	Signaling Colors		Catalog No.
			Steady	Flashing	
For support tube mounting, 17mm					
Without buzzer	LED for steady light only	24 VAC/DC	R	-	XVC 4B1
			R, O	-	XVC 4B2
			R, O, G	-	XVC 4B3
			R, O, G, B	-	XVC 4B4
			R, O, G, B, C	-	XVC 4B5
With buzzer	LED for steady or flashing light	24 VAC/DC	R	R	XCV 4B15S
			R, O	R, O	XCV 4B25S
			R, O, G	R, O, G	XCV 4B35S
			R, O, G, B	R, O, G, B	XCV 4B45S
			R, O, G, B, C	R, O, G, B, C	XCV 4B55S
For base mounting					
Without buzzer	LED for steady light only	24 VAC/DC	R	-	XCV 4B1K
			R, O	-	XCV 4B2K
			R, O, G	-	XCV 4B3K
			R, O, G, B	-	XCV 4B4K
			R, O, G, B, C	-	XCV 4B5K

Product Offering, continued



Complete, pre-wired Tower Lights Ø 60mm Diameter

Description	Light Source (included)	Voltage V	Signaling Colors		Catalog No.
			Steady	Flashing	
For support tube mounting, 22mm					
Without buzzer	LED for steady light only	24 VAC/DC	R	-	XVC 6B1
			R, O	-	XVC 6B2
			R, O, G	-	XVC 6B3
			R, O, G, B	-	XVC 6B4
			R, O, G, B, C	-	XVC 4B5
With buzzer	LED for steady or flashing light	24 VAC/DC	R	R	XCV 6B15S
			R, O	R, O	XCV 6B25S
			R, O, G	R, O, G	XCV 6B35S
			R, O, G, B	R, O, G, B	XCV 6B45S
			R, O, G, B, C	R, O, G, B, C	XCV 6B55S
For base mounting					
Without buzzer	LED for steady light only	24 VAC/DC	R	-	XCV 6B1K
			R, O	-	XCV 6B2K
			R, O, G	-	XCV 6B3K
			R, O, G, B	-	XCV 6B4K
			R, O, G, B, C	-	XCV 6B5K
With buzzer	LED for steady light only	24 VAC/DC	R	R	XCV 6B15SK
			R, O	R, O	XCV 6B25SK
			R, O, G	R, O, G	XCV 6B35SK
			R, O, G, B	R, O, G, B	XCV 6B45SK
			R, O, G, B, C	R, O, G, B, C	XCV 6B55SK

Complete, pre-wired Tower Lights Ø 100mm Diameter

Description	Light Source (included)	Voltage V	Signaling Colors		Catalog No.
			Steady	Flashing	
For base mounting					
Without buzzer	LED for steady or flashing light	24VDC	R	R	XVC 1B1K
			R, O	R, O	XVC 1B2K
			R, O, G	R, O, G	XVC 1B3K
			R, O, G, B	R, O, G, B	XVC 1B4K
			R, O, G, B, C	R, O, G, B, C	XVC 1B5K
With buzzer	LED for steady or flashing light	24VDC	R	R	XCV 1B18K
			R, O	R, O	XCV 1B28K
			R, O, G	R, O, G	XCV 1B38K
			R, O, G, B	R, O, G, B	XCV 1B48K
			R, O, G, B, C	R, O, G, B, C	XCV 1B58K

Schneider Electric - North American Operating Division

1415 S. Roselle Road
 Palatine, IL 60067
 Tel: 847-397-2600
 Fax: 847-925-7500